

FT型 黃銅鍍鎳電纜固定頭

一般環境用



產品說明

材質說明 金屬部分為黃銅鍍鎳，夾緊爪為尼龍 PA66，密封圈NBR橡膠

防護等級 在規定電纜範圍內，使用密封圈旋轉迫緊固定頭，達IP68

適用溫度 靜態：-40℃到+110℃，瞬間溫度+120℃
動態：-20℃到+80℃，短時間達+100℃

M牙 規格表

型號	螺紋規格	電纜範圍 Ø	外徑 AG	牙長 GL	板手直徑
FT6-M10	M10x1.5	2-6	10	6	14
FT5-M12	M12x1.5	3-5.3	12	8	17
FT6S-M12	M12x1.5	2-6	12	8	17/14
FT8-M12	M12x1.5	4.5-7.8	12	8	17
FT6-M16	M16x1.5	4-7	16	9	20
FT8S-M16	M16x1.5	4.5-7.8	16	9	20/17
FT10-M16	M16x1.5	6-10	16	9	20
FT10S-M20	M20x1.5	6-10	20	9.5	24
FT12S-M20	M20x1.5	8-12	20	9.5	24
FT14-M20	M20x1.5	9-14	20	9.5	26
FT16-M25	M25x1.5	12-16	25	12	30
FT18-M25	M25x1.5	14-18	25	12	30
FT18-M30	M30x1.5(2.0)	14-18	30	12	34/32
FT22-M32	M32x1.5	16-22	32	12.5	38/40
FT25-M32	M32x1.5	18-25	32	12.5	38/40
FT25-M36	M36x1.5(2.0)	18-25	36	12.5	40
FT25-M40	M40x1.5	21-25	40	15	50
FT30-M40	M40x1.5	24-30	40	15	50
FT30-M42	M42x2.0	24-30	42	15	50
FT30-M48	M48x2.0	24-30	48	15	52/50
FT32-M50	M50x1.5	26-32	50	15	60
FT39-M50	M50x1.5	36-41	50	15	60
FT44-M60	M60x2.0	36-44	60	15	70/65
FT44-M63	M63x1.5	36-44	63	15	70/65
FT46-M63	M63x1.5	40-46	63	15	70/65
FT54-M63	M63x1.5	47-53.5	63	15	75/70
FT44-M64	M64x2.0	36-44	64	15	70/65
FT54-M72	M72x2.0	47-53.5	50	15	80/75
FT66-M75	M75x2.0	56-66	75	15	90/85
FT77-M90	M90x2.0	66-77	90	15	100

PG牙 規格表

型號	螺紋規格	電纜範圍 Ø	外徑 AG	牙長 GL	板手直徑
FT6S-PG7	PG7	2-6	12.5	8	14
FT5-PG7	PG7	3-5.3	12.5	8	17
FT8-PG7	PG7	4.5-7.8	12.5	8	17
FT5-PG9	PG9	3-5.3	15.2	8	17
FT8-PG9	PG9	4.5-7.8	15.2	8	17
FT6-PG11	PG11	4-7	18.6	9	20
FT10-PG11	PG11	6-10	18.6	9	20
FT9-PG13.5	PG13.5	5.5-9	20.4	9.5	24
FT10-PG13.5	PG13.5	6-10	20.4	9.5	24
FT12-PG13.5	PG13.5	8-12	20.4	9.5	24
FT10-PG16	PG16	7-11	22.5	9.5	26
FT14-PG16	PG16	9-14	22.5	9.5	26
FT16-PG21	PG21	12-16	28.3	12	30
FT18-PG21	PG21	14-18	28.3	12	30
FT22-PG29	PG29	16-22	37	12.5	40
FT25-PG29	PG29	18-25	37	12.5	40
FT25-PG36	PG36	18-25	47	15	52/50
FT30-PG36	PG36	24-30	47	15	52/50
FT30-PG42	PG42	24-30	54	15	60
FT41-PG42	PG42	31-41	54	15	66/60
FT44-PG48	PG48	38-44	59.3	15	70/65

NPT牙 規格表

型號	螺紋規格	電纜範圍 Ø	外徑 AG	牙長 GL	板手直徑
FT5-NPT3/8	NPT3/8	3-5.3	17.05	8	20
FT8-NPT3/8	NPT3/8	4-8	17.05	8	20
FT9-NPT1/2	NPT1/2	5.5-9	21.22	9	24
FT12-NPT1/2	NPT1/2	8.5-12	21.22	9	24
FT16-NPT3/4	NPT3/4	12-16	26.56	12	30
FT18-NPT3/4	NPT3/4	14-18	26.56	12	30
FT22-NPT1	NPT1	15-22	33.23	15	40
FT25-NPT1	NPT1	18-25	33.23	15	40
FT25-NPT1-1/4	NPT1-1/4	18-25	41.98	15	50
FT30-NPT1-1/4	NPT1-1/4	24-30	41.98	15	50
FT25-NPT1-1/2	NPT1-1/2	18-25	48.05	15	52/50
FT30-NPT1-1/2	NPT1-1/2	24-30	48.05	15	52/50
FT44-NPT2	NPT2	38-44	60.09	15	65

G/PF牙 規格表

型號	螺紋規格	電纜範圍 Ø	外徑 AG	牙長 GL	板手直徑
FT6-G1/4	G1/4	2-6	13.15	8	17
FT8-G1/4	G1/4	4.5-7.8	13.15	8	17
FT5-G3/8	G3/8	3-5.3	16.66	9	18
FT8-G3/8	G3/8	4-8	16.66	9	18
FT9-G1/2	G1/2	5.5-9	20.99	9	24
FT10-G1/2	G1/2	6-10	20.99	9	24
FT12-G1/2	G1/2	8.5-12	20.99	9	24
FT14-G1/2	G1/2	10-14	20.99	9	26
FT16-G3/4	G3/4	12-16	26.44	12	30
FT18-G3/4	G3/4	14-18	26.44	12	30
FT22-G1	G1	15-22	33.25	12	40
FT25-G1	G1	18-25	33.25	12	40
FT25-G1-1/4	G1-1/4	18-25	41.91	15	50
FT30-G1-1/4	G1-1/4	24-30	41.91	15	50
FT25-G1-1/2	G1-1/2	18-25	47.8	15	52/50
FT30-G1-1/2	G1-1/2	24-30	47.8	15	52/50
FT44-G2	G2	38-44	59.61	15	65
FT66-G2-1/2	G2-1/2	56-66	75.18	15	90/85

單位：mm。本公司保留改變結構尺寸的權利