


# FT-M-F型 接管式電纜固定頭

一般環境用



產品說明

### 特點說明

此款設計適合鍍鋅鋼管接管

### 材質說明

金屬部分為304不鏽鋼 (可訂製316、316L不鏽鋼)

### 螺牙規格

公制M牙、PG牙、G(PF)牙以及NPT牙

### 防護等級

在規定電纜範圍內，使用密封圈旋轉迫緊固定頭，達IP68

### 適用溫度

-40°C~+100°C 短時達+120°C

## FT-M-F-SS 規格表 (不鏽鋼)

型號 選擇螺紋規格並代入※	外螺紋規格				內螺紋規格			電纜 範圍	牙長 GL	板手 直徑
	M牙	M牙	G牙	NPT牙	M牙	G牙	NPT牙			
FT8-※M-※F-SS	M12x1.5	M14x1.5	G1/4	NPT1/4	M12x1.5	G1/4	NPT1/4	4.5-7.8	8/12	17
FT10-※M-※F-SS	M16x1.5	/	G3/8	NPT3/8	M16x1.5	G3/8	NPT3/8	6-10	9/12	20
FT10-※M-※F-SS	M18x1.5	/	/	/	M18x1.5	/	/	6-10	9/12	20
FT10-※M-※F-SS	M20x1.5	M21x1.5	G1/2	NPT1/2	M20x1.5	G1/2	NPT1/2	6-10	10/12	24
FT12-※M-※F-SS	M20x1.5	M22x1.5	G1/2	NPT1/2	M20x1.5	G1/2	NPT1/2	8-12	10/12	24
FT14-※M-※F-SS	M20x1.5	M24x1.5	G1/2	NPT1/2	M20x1.5	G1/2	NPT1/2	9-14	10/12	26
FT16-※M-※F-SS	M25x1.5	M27x1.5	G3/4	NPT3/4	M25x1.5	G3/4	NPT3/4	12-16	12/12	30
FT18-※M-※F-SS	M25x1.5	M30x1.5	G3/4	NPT3/4	M25x1.5	G3/4	NPT3/4	14-18	12/12	30
FT22-※M-※F-SS	M32x1.5	M33x2	G1	NPT1	M32x1.5	G1	NPT1	16-22	12.5/15	38/40
FT25-※M-※F-SS	M32x1.5	M36x2	G1	NPT1	M32x1.5	G1	NPT1	18-25	12.5/15	38/40
FT30-※M-※F-SS	M40x1.5	M42x2	G1-1/4	NPT1-1/4	M40x1.5	G1-1/4	NPT1-1/4	24-30	15/15	50
FT41-※M-※F-SS	M50x1.5	M48x2	G1-1/2	NPT1-1/2	M40x1.5	G1-1/2	NPT1-1/2	31-41	15/15	50
FT44-※M-※F-SS	M63x1.5	M60x2	G2	NPT2	M63x1.5	G2	NPT2	37-44	15/15	70/65