

SSJ-SS型 雙鎖緊電纜固定頭

一般環境用



產品說明

材質說明

金屬部分為黃銅鍍鎳、304不鏽鋼
(可訂製316、316L不鏽鋼)

防護等級

在規定電纜範圍內，使用密封圈旋轉迫緊固定頭，
達IP68

適用溫度

-40°C到+110°C，瞬間溫度120°C



SSJ-SS 規格表 (不鏽鋼)

型號 選擇螺紋並代入※	螺紋規格				電纜範圍 Ø	牙長 GL
	M牙	PG牙	G牙	NPT牙		
SSJ5-※-SS	M12×1.5, M14×1.5	PG7	G1/4	NPT1/4	3-5.3	8
SSJ8-※-SS	M12×1.5	PG7, PG9	G1/4	NPT1/4	4.5-7.8	8
SSJ8-※-SS	M14×1.5	PG7, PG9	G1/4	NPT1/4	4.5-7.8	8
SSJ8-※-SS	M16×1.5	PG7, PG9	G1/4	NPT1/4	4.5-7.8	8
SSJ6-※-SS	M16×1.5	PG9, PG11	G3/8	NPT3/8	4-7	9
SSJ10-※-SS	M16×1.5, M18×1.5	PG9, PG11	G3/8	NPT3/8	6-10	9
SSJ9S-※-SS	M20×1.5	PG13.5	G1/2	NPT1/2	5.5-9	9.5
SSJ10S-※-SS	M20×1.5	PG13.5	G1/2	NPT1/2	6-10.5	9.5
SSJ12S-※-SS	M20×1.5	PG13.5	G1/2	NPT1/2	8-12	9.5
SSJ14-※-SS	M20×1.5, M21×1.5	PG13.5, PG16	G1/2	NPT1/2	9-14	9.5
SSJ14-※-SS	M22×1.5, M24×1.5	PG13.5, PG16	G1/2	NPT1/2	9-14	9.5
SSJ16-※-SS	M20×1.5, M25×1.5	PG21	G3/4	NPT3/4	12-16	12
SSJ16-※-SS	M27×1.5(2.0), M30×1.5(2.0)	PG21	G3/4	NPT3/4	12-16	12
SSJ18-※-SS	M25×1.5, M27×1.5(2.0)	PG21	G3/4	NPT3/4	14-18	12
SSJ18-※-SS	M30×1.5(2.0)	PG21	G3/4	NPT3/4	14-18	12
SSJ22-※-SS	M32×1.5, M33×2.0	PG29	G1	NPT1	17-22	12.5
SSJ22-※-SS	M36×1.5(2.0)	PG29	G1	NPT1	17-22	12.5
SSJ25-※-SS	M32×1.5, M33×2.0	PG29	G1	NPT1	18-25	12.5
SSJ25-※-SS	M36×1.5(2.0)	PG29	G1	NPT1	18-25	12.5
SSJ25-※-SS	M40×1.5, M42×2.0	PG36	G1-1/4, G1-1/2	NPT1-1/4, NPT1-1/2	21-25	15
SSJ25-※-SS	M48×2.0	PG36	G1-1/4, G1-1/2	NPT1-1/4, NPT1-1/2	21-25	15
SSJ30-※-SS	M40×1.5, M42×2.0	PG36	G1-1/4, G1-1/2	NPT1-1/4, NPT1-1/2	24-30	15
SSJ30-※-SS	M48×2.0	PG36	G1-1/4, G1-1/2	NPT1-1/4, NPT1-1/2	24-30	15
SSJ32-※-SS	M50×1.5	PG42	G1-1/4, G1-1/2	NPT1-1/4, NPT1-1/2	26-32	15
SSJ39-※-SS	M50×1.5	PG42	G1-1/4, G1-1/2	NPT1-1/4, NPT1-1/2	32-41	15
SSJ44-※-SS	M60×2.0, M63×1.5	PG48	G2	NPT2	36-44	15
SSJ44-※-SS	M64×2.0	PG48	G2	NPT2	36-44	15