

KS-AD型 浪管快接式電纜固定頭

一般環境用



產品說明

特點說明

快接式浪管夾緊設計，使浪管方便拆卸

材質說明

金屬部分為黃銅鍍鎳或304不鏽鋼(可訂製316、316L不鏽鋼)，黑色外殼和夾緊爪為尼龍PA66，密封圈為NBR橡膠

防護等級

在規定電纜範圍內旋緊迫固定頭，達IP65

適用溫度

-40°C~+100°C 短時達+120°C



KS-AD-SS 規格表 (不鏽鋼)

型號 選擇螺紋規格並代入※	浪管尺寸 AD	電纜範圍 Ø	外螺紋規格				牙長 GL
			M牙	G牙	NPT牙	PG牙	
KS 6-※-AD10.0-SS	AD10.0	2-6	M12×1.5	G1/4	NPT 1/4	PG7	8
KS 8-※-AD13.0-SS	AD13.0	4.5-7.8	M12×1.5, M16×1.5	G3/8	NPT 3/8	PG7, PG9	8
KS 10-※-AD15.8-SS	AD15.8	6-10	M16×1.5	G3/8	NPT 3/8	PG11	9
KS 9-※-AD15.8-SS	AD15.8	5.5-9	M20×1.5	G1/2	NPT 1/2	PG13.5	10
KS 10-※-AD15.8-SS	AD15.8	6-10	M20×1.5	G1/2	NPT 1/2	PG13.5	10
KS 12-※-AD15.8-SS	AD15.8	8-12	M20×1.5	G1/2	NPT 1/2	PG13.5	10
KS 12-※-AD18.5-SS	AD18.5	8-12	M20×1.5	G1/2	NPT 1/2	PG13.5	10
KS 14-※-AD15.8-SS	AD18.5	9-14	M20×1.5, M22×1.5, M24×1.5	G1/2	NPT 1/2	PG13.5	10
KS 12-※-AD21.2-SS	AD21.2	8-12	M20×1.5	G1/2	NPT 1/2	PG13.5	10
KS 14-※-AD21.2-SS	AD21.2	9-14	M20×1.5, M22×1.5, M24×1.5	G1/2	NPT 1/2	PG13.5, PG16	10
KS 14-※-AD21.2-SS	AD21.2	9-14	M20×1.5, M22×1.5, M24×1.5	G1/2	NPT 1/2	PG13.5, PG16	10
KS 16-※-AD21.2-SS	AD21.2	12-16	M25×1.5, M27×1.5, M30×1.5	G3/4	NPT 3/4	PG21	10
KS 14-※-AD21.2-SS	AD25.0	9-14	M20×1.5, M22×1.5, M24×1.5	G1/2	NPT 1/2	PG13.5	10
KS 16-※-AD25.0-SS	AD25.0	12-16	M25×1.5, M27×1.5, M30×1.5	G3/4	NPT 3/4	PG21	12
KS 18-※-AD25.0-SS	AD25.0	14-18	M25×1.5, M27×1.5, M30×1.5	G3/4	NPT 3/4	PG21	12
KS 18-※-AD28.5-SS	AD28.5	14-18	M25×1.5, M27×1.5, M30×1.5	G3/4	NPT 3/4	PG21	12
KS 22-※-AD25.0-SS	AD28.5	17-22	M32×1.5, M33×1.5, M36×1.5	G1	NPT 1	PG29	12.5
KS 22-※-AD25.0-SS	AD34.5	17-22	M32×1.5, M33×1.5, M36×1.5	G1	NPT 1	PG29	12.5
KS 25-※-AD34.5-SS	AD34.5	18-25	M32×1.5, M33×1.5, M36×1.5	G1	NPT 1	PG29	12.5
KS 25-※-AD42.5-SS	AD42.5	18-25	M32×1.5, M33×1.5, M36×1.5	G1	NPT 1	PG29	12.5
KS 25-※-AD42.5-SS	AD42.5	21-25	M40×1.5, M42×2.0, M48×2.0	G1-1/4	NPT 1-1/4	PG36	15
KS 25-※-AD42.5-SS	AD42.5	21-25	M40×1.5, M42×2.0, M48×2.0	G1-1/2	NPT 1-1/2	PG36	15
KS 30-※-AD42.5-SS	AD42.5	24-30	M40×1.5, M42×2.0, M48×2.0	G1-1/4	NPT 1-1/4	PG36	15
KS 30-※-AD42.5-SS	AD42.5	24-30	M40×1.5, M42×2.0, M48×2.0	G1-1/2	NPT 1-1/2	PG36	15
KS 30-※-AD54.5-SS	AD54.5	24-30	M40×1.5, M42×2.0, M48×2.0	G1-1/4	NPT 1-1/4	PG36	15
KS 30-※-AD54.5-SS	AD54.5	24-30	M40×1.5, M42×2.0, M48×2.0	G1-1/2	NPT 1-1/2	PG36	15
KS 32-※-AD54.5-SS	AD54.5	25-32	M50×1.5, M54×2.0	/	/	PG42	15
KS 41-※-AD54.5-SS	AD54.5	31-41	M50×1.5	/	/	PG42	15
KS 44-※-AD54.5-SS	AD54.5	38-44	M60×2.0, M63×1.5, M64×2.0	G2	NPT 2	PG48	15